

visprox

GP 5500

GENERAL DATA	DESCRIPTION	Vinyl solvent-based ink with glossy finish
	SUBSTRATES	Paper, ABS, PVC, PES, PC, PET, PET-G, PMMA
	APPLICATION	SCREEN PRINTING
	FEATURES	Excellent printability
		Excellent stability in the screen
		Excellent flexibility
		Good opacity
		Good chemical resistance

TECHNICAL DATA	SCREEN PRINTING	
	MESH	Max 165 Th/cm
	PHOTOEMULSION	COATING SERIES
	SQUEEGEE	70-75 shores
	DRYING	20 minutes at room temperature
		2 minutes at 50-60°C
	THINNERS	THINNER 11 (code VXTH11L1 e VXTH11L5) THINNER 10 (code VXTH10L1 e VXTH10L5) RETARDER 4 (code VXTH4L1 e VXTH4L5) RETARDER 8 (code NTH8L1 e NTH8L5)
	ADDITIVES	GELRETARDER C.L. (code VXGELRETARDCLL1 and VXGELRETARDCLL5) GELTHINNER (code VXGELTHINNERL1) CONCENTRATED ANTI CRATER 0.1-0.5 % (code VXKRATERL0.1 and VXKRATERL0.5)
	HARDENERS	HARDENER N.2 (NHR908N0.1)
	CLEANING	CLEANER 920 (NCL920L5) CLEANER 920 (NCL920L25) CLEANER 920 (NCL920L180)

PREPARATION	SCREEN PRINTING	
	Before using, the ink must be well mixed and in case diluted, according to the printing requirements.	
	In order to increase adhesion onto such substrates, that are hard to be printed, add up to 10% of HARDENER N.2 . Through the addition of such promoter, the ink has a pot-life of about 8 hours.	
	For spray application, it is recommended to dilute the ink through THINNER 11 .	

visprox

GP 5500

COLOUR RANGE	OPAQUE COLOURS			COLOURMATIC		
	CODE	COLOUR	PACKAGE	CODE	COLOUR	PACKAGE
	VX5506L1	GP 5506 MEDIUM YELLOW	1 l	VX5501LL1	GP 5501 L WHITE	1 l
	VX5507L1	GP 5507 BRIGHT ORANGE	1 l	VX5501LL5	GP 5501 L WHITE	5 l
	VX5510L1	GP 5510 BRIGHT RED	1 l	VX5502ML1	GP 5502 M BLACK	1 l
	VX5515L1	GP 5515 SKY BLUE	1 l	VX5502ML5	GP 5502 M BLACK	5 l
	VX5527L1	GP 5527 BLUE	1 l	VX5500AL1	GP 5500 A LEMON YELLOW	1 l
	VX5538L1	GP 5538 BRILLANT GREEN	1 l	VX5500BL1	GP 5500 B GOLDEN YELLOW	1 l
	VX5539L1	GP 5539 SPRING GREEN	1 l	VX5500CL1	GP 5500 C ORANGE	1 l
	VX5528L1	GP 5528 CHROME YELLOW	1 l	VX5500DL1	GP 5500 D RED	1 l
COLOUR RANGE	VX5540L1	GP 5540 RED	1 l	VX5500EL1	GP 5500 E CARMINE	1 l
	VX5530L1	GP 5530 RUBY RED	1 l	VX5500FL1	GP 5500 F PINK	1 l
	VX5536L1	GP 5536 OPAQUE PINK	1 l	VX5500GL1	GP 5500 G BRIGHT VIOLET	1 l
	VX5542L1	GP 5542 DARK BLUE	1 l	VX5500HL1	GP 5500 H PERM.BLUE	1 l
	VX5560L1	GP 5560 VIOLET	1 l	VX5500KL1	GP 5500 K PERM.GREEN	1 l
	FOUR-COLOUR PROCESS			BIANCHI, NERI E TRASPARENTI		
	CODE	COLOUR	PACKAGE	CODE	COLOUR	PACKAGE
	VX5550L1	GP 5550 BASE TIX	1 l	VX5502EOL1	GP 5502 EO BLACK	1 l
	VX5551L1	GP 5551 YELLOW TIX	1 l	VX5502EOL5	GP 5502 BLACK EO	5 l
	VX5552L1	GP 5552 CYAN TIX	1 l	VX5501EOL1	GP 5501 EO WHITE	1 l
COLOUR RANGE	VX5553L1	GP 5553 MAGENTA TIX	1 l	VX5501EOL5	GP 5501 EO WHITE	5 l
	VX5554L1	GP 5554 BLACK TIX	1 l	VX5501SOL1	GP 5501 WHITE SUPER OPAQUE	1 l
				VX5549L1	GP 5549 CLEAR	1 l
	OTHER PRODUCTS			AUXILIARIES		
	CODE	COLOUR	PACKAGE	CODE	COLOUR	PACKAGE
	VX5547L1	GP 5547 SILVER	1 l	VXMATPASTAL1	MATTERINGS PASTA	1 l
				VXMATPASTAL5	MATTERINGS PASTA	5 l

STORAGE

The products, kept in their sealed original packages, have a shelf-life of two years.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk. While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.