

## SERIPLASTIK CLEAR BASES AND 3D EFFECTS

### 1 DESCRIPTION

The bases and transparent inks hereunder are consistent with all products of **SERIPLASTIK** series

### 2 PRODUCTS

	CODE	FEATURES	USE
<b>NAME</b>		<b>SERIPLASTIK TRASPARENTE DA TAGLIO</b>	
DESCRIPTION	<b>12.990</b>	Neutral plastisol base for shade softening of four-colour process or reduction of opaque colour intensity.	According to the results to be achieved.
<b>NAME</b>		<b>SERIPLASTIK BASE TRASPARENTE EFFETTOLENTE</b>	<b>SERIPLASTIK BASE TRASPARENTE EFFETTOLENTE</b>
DESCRIPTION	<b>12.889</b>	Plastisol transparent base for the realization of high thickness printing with a glossy and very transparent effect. The achieved printing effect is "convex" like a "lens".	may be printed on the fabric directly, or may be overprinted over any colour of <b>SERIPLASTIK</b> series.
<b>NAME</b>		<b>SERIPLASTIK BASE GLOSS 9544</b>	
DESCRIPTION	<b>12.891</b>	Plastisol transparent base for the creation of special effects. It may be used in combination with glitters, metal powders, pearly powders, and transparent cover beats. The number of threads/cm of the screen to be used depends on the effect to be achieved.	<b>% GLITTERS TO BE MIXED:</b> [1% - 20%].
<b>NAME</b>		<b>SERIPLASTIK BASE GLOSS ALTO SPESSORE 77.1030D</b>	
DESCRIPTION	<b>12.892</b>	Plastisol high viscosity transparent base. It may be used to obtain very glossy and transparent "square edge" printing.	<b>SERIPLASTIK BASE GLOSS ALTO SPESSORE 77.1030D</b> may be printed on fabric directly.
<b>NAME</b>		<b>SERIPLASTIK BASE SOFT</b>	
DESCRIPTION	<b>09.996</b>	Plastisol neutral base for the realisation of soft touch and tack-free printing. It may be used as a print protection finishing or as a primer on transfer paper, in order to aid hot peeling.	<b>% ADDED TO THE COLOURS:</b> [10% - 20%]
<b>NAME</b>		<b>SERIPLASTIK ROCK BASE</b>	
DESCRIPTION	<b>69.993</b>	Plastisol high viscosity transparent base. It may be used to obtain glossy and transparent "square edge" printing.	<b>SERIPLASTIK ROCK BASE</b> may be printed on fabric directly.

3

### APPLICATION

Refer to the Technical Data Sheets of the corresponding series (**SERIPLASTIK**).

4

### STORAGE

We suggest keeping the products at a temperature between 18°C and 30°C, away from sunlight.

### IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk. While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development